

LANTICK

2-2, 0-4



Applications:

- Monitoring the state of a digital input via LAN
- Remote relay output control (PE-2-2)
- Integration with building management, monitoring and alarm systems
- Remote system diagnostics

Characteristics:



- Robust construction for reliability and durability of the device.
- Easy to use user interface.
- Built-in www server for remote device management and configuration via a web browser.
- HTTP, Modbus TCP, SNMP, TCP/UDP, KNX/IP, Inveo Dashboard communication protocols support.
- Expandable and scalable as the system grows.

Technical characteristics

Power supply	Passive PoE 10-24V DC	DC: 12-24V DC, 3,5mm screw terminal	
Power consumption	Max. 1,5W		
Outputs (Lantick PE-2-2)	Output type: NO/NC relay	Maximum load: 4A	
	Operating modes: bistable, astable, monostable (single trigger)	Maximum voltage: 250V AC	
Inputs	Input type: NO, potential-less, pre-polarized or voltage	Maximum counter value: 4 294 967 296	Maximum input frequency: 1000Hz
Communication	Ethernet 10Mbps, RJ45 port		
Enclosure	IP rating: IP30	Dimensions: 90 x 52,5 x 65mm	
Operating temperature	From -10°C to +55°C		

Version	Inputs	Outputs	Catalogue number
Lantick PE-2-2	2	2	LN-0008-2041-00
Lantick PE-0-4	4	-	LN-0001-2002-00